

## Technical Data Sheet

## Leunapon-XF 11 - preliminary

### General product information

<b>Product name</b>	<b>Leunapon-XF 11 – preliminary</b>
<b>Chemical name</b>	Oxirane, 2-methyl-, polymer with oxirane, mono(2-propylheptyl) ether
<b>CAS number</b>	166736-08-9
<b>EINECS number</b>	Polymer
<b>Registration number</b>	As a polymer the product is excluded from the registration, evaluation, authorization and restriction of chemicals (EC) No. 1907/2006 (REACH).
<b>Customs tariff number</b>	3402 13 00

### Specifications (parameters quoted on CoA)

Characteristics	Unit	Target value	Applied method
Cloud point (5 g + 25 g BDG 25 % sol.)	°C	67 – 71	DIN EN 1890
Water	%	≤ 0,2	DIN 51 777
pH value (5 % sol.)		5 – 8	DIN EN 1262

### Additional information

Appearance at 25 °C	liquid, cloudy
Active content	≥ 99,8 %
HLB (calculated)	12,5
Hydroxyl value	110 – 120 mg KOH/g (DIN EN 53 240)

The information provided in this document is based on the best of our knowledge and experience. It is intended as a general description of our product specifications and shall not constitute a guarantee or agreement regarding the quality of the specified products, respectively. The customer remains responsible for the inspection and testing of the specified products, as well as any supplementary information and documents provided alongside with the specified products, in particular the material safety data sheets, in order to determine their suitability for their particular application.

## Technical Data Sheet

## Leunapon-XF 11 - preliminary

### Storage and Handling

Store in dry and cool conditions and protect the product from heat and direct sunlight. In enclosed original container product keeps stable for at least 2 years.

Prior taking portions all the lot must be homogenised.

Please refer to the Safety Data Sheet (SDS) for this product for instructions on safe and proper handling and disposal.

### Packaging

<b>Bulk</b>	5 – 24 t
<b>IBC</b>	850 kg
<b>steel-drum</b>	180 kg

	Laboratory	Production	Marketing
Date			
Signed by	Schmidt	Enke	Grevesmühl
Version	11/20		