



## Technical Data Sheet

## RustSafe™ 2400 Corrosion Inhibitor

### Product Description

**RustSafe 2400** Corrosion Inhibitor is a solvent based, water displacing corrosion inhibitor designed to rapidly separate from typical water based solutions used in machining operations or cleaning systems. RustSafe 2400 leaves a dry, ultra-thin film capable of protecting all metal surfaces for over 60 days even when stored outdoors or in high humidity environments.

### Features and Benefits

- Non-Staining
- Ultra-Thin Film
- Non-Emulsifying
- Easily Cleaned
- Water Displacing
- Dry to the Touch

### Properties

Odor	Mild
Specific Gravity (25 °C)	0.81

### Equipment

Suitable for use in a variety of cleaning equipment, including dip tank systems and mechanically agitated immersion tanks.

### Process

1. Add RustSafe 2400 to the tank reservoir at full concentration
2. Immerse parts in RustSafe 2400 for 1-2 minutes or until the parts are adequately covered.
3. After the immersion process, allow the parts to drip dry up to 8 hours. Drying can be accelerated using a high pressure air stream.
4. Periodically check the drainage tap near the bottom of your tank reservoir for water accumulation. If necessary, remove any water present and replenish the tank with RustSafe 2400.

### Disposal/Safety

#### Disposal

Vantage recommends contacting your current or local environmental service company for proper disposal.

#### Safety

Please see Safety Data Sheet for further information.

### Packaging

Available in 33 lb (15 kg) pail and 370 lb (169 kg) drums

### Shelf Life

36 months when stored in original, sealed container above 50°F (10°C).



## Technical Data Sheet

## RustSafe™ 2400 Corrosion Inhibitor



ISO 9001:2008



RustSafe is a trademark of Vantage Specialties, Inc.

Typical property data is not intended for specification purposes. Vantage Specialties, Inc., its sales agents and distributors make no warranty of merchantability of the product or of product fitness for any particular purpose. This product and all information supplied are used at the purchaser's own risk. The purchaser assumes all risk of use or handling of the product, whether in accordance with directions or not.

Vantage Specialties, Inc.

3938 Porett Drive • Gurnee, Illinois 60031 USA • P +1 847 244 3410 • F +1 847 249 6346 • [www.vantagegrp.com](http://www.vantagegrp.com)